
Claims

What is claimed as new is as follows:

1. In combination with a swing typically including an elongated horizontal transverse seat suspended at its opposite ends from the lower ends of a single pair of dependently supported suspension members including means of anchorage at their lower ends and therefore anchored to those seat ends, an adapter for said seat including opposite non rigid flexible and conforming cloth side panels each having two adjustable nylon straps with one strap attached to the top middle and one strap attached to the bottom middle of the side cloth panel, with each strap featuring slide latching anchor hooks on their ends, a non rigid flexible and conforming cloth front panel with two orifices designed to function as outlets for the users legs, with an adjustable nylon strap attached at waist height similar to a typical seat belt on both side areas of the cloth front panel, and also having a adjustable nylon strap attached in the lower middle crotch area of the cloth panel, and a cloth back panel made rigid via a removable plastic insert located within a insert pocket of the back cloth panel, with the plastic insert hinged in such a manner that it can rotate upon its hinge from a folded upon itself position to a rotated 90 degree chair type right angle position thus providing rigidity and support in the users buttocks, and the users lower and upper back areas, with the opposite sides, front, and back, cloth panels sewn together in such a manner as to provide a protective restraining enclosure.
2. The combination of claim 1 wherein the strap of the crotch area of the cloth front panel is designed so that it may be wrapped around the swings seat and adjusted via its buckle mechanism to secure it, with the upper middle and the lower middle straps of the side panels designed so that they may be attached to, and secured to, the suspension members of the swing via the slide latching anchor hooks at the straps ends, and positioned so that the internal plastic insert of the adapter is rotated into the 90 degree right angle position, with said straps adjustable via their respective buckle mechanisms to secure that position, allowing placement of the user within the adapter enclosure carefully guiding the child's legs through the outlet orifices of the front cloth panel , and then the adjustment of the front panel waist strap which provides final securement of the child within the adapter which is now securely mounted to the swing.